

# Luxus SIS 109004

Styrene Isoprene Styrene Block Copolymer

Luxus Limited

## Message:

A fully recycled impact modifier for the polymer recycling industry, the modifier demonstrates good results in Polypropylene, Polyethylene, Polystyrene. With low viscosity and high strength properties the impact modifier is easy to incorporate into compounds or directly on a moulding machine. It has a natural/white colouring and will readily turn to most colours.

General Information			
Recycled Content	Yes		
Features	High Strength		
	Low Viscosity		
Uses	Plastics Modification		
Appearance	Natural Color		
	White		

Physical	Nominal Value	Unit	Test Method
Density	0.930	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR)	15 to 20	g/10 min	ISO 1133

Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D)	49		ISO 868

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

