

ExxonMobil™ SFT325

Polypropylene Homopolymer

ExxonMobil Chemical

Message:

A high-quality homopolymer resin can be applied to the production of high-speed spunbond technology with good fluid barrier to spin non-woven fabrics with soft cotton texture.

General Information			
Features	Narrow molecular weight distribution		
Uses	Spunbond nonwoven fabric		
	Personal care		
	Medical/nursing supplies		
Appearance	Natural color		
Forms	Particle		
Processing Method	Spunbond Nonwovens		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	45	g/10 min	ASTM D1238
Legal statement			

本产品不宜在与食品接触的应用中使用.未经埃克森美孚化工书面允许,这种产品包括其产品名称,不得在任何医疗应用领域予以使用或

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

