

Geon™ Vinyl Flexible R352AE

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™ Vinyl Flexible R352AE is a Flexible Polyvinyl Chloride product. It can be processed by extrusion, injection molding, or profile extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Applications of Geon™ Vinyl Flexible R352AE include automotive and marine applications. Primary characteristic: uv stabilized.

General Information	
Additive	UV Stabilizer
Features	General Purpose
	UV Absorbing
Uses	Automotive Bumper
	General Purpose
	Marine Applications
	Profiles
Forms	Pellets
Processing Method	Extrusion
	Injection Molding
	Profile Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.37	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	79		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Break)	15.9	MPa	ASTM D638
Tensile Elongation ² (Break)	300	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-35.0	°C	ASTM D746
Injection	Nominal Value	Unit	
Processing (Melt) Temp	193 to 204	°C	
Extrusion	Nominal Value	Unit	
Melt Temperature	174 to 179	°C	
NOTE			
1.	Type IV, 510 mm/min		
2.	Type IV, 510 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

