

# Geon™ CPVC EC4911

Chlorinated Polyvinyl Chloride

PolyOne Corporation

## Message:

The Geon EC4911 is a CPVC compound for extrusion applications.

General Information			
Uses	Industrial Applications		
Forms	Powder		
Processing Method	Sheet Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.53	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	76		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus (23°C)	2520	MPa	ASTM D638
Tensile Strength (Yield, 23°C)	49.6	MPa	ASTM D638
Flexural Strength (Yield)	89.0	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 3.18 mm)	160	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Annealed)	78.5	°C	ASTM D648
Extrusion	Nominal Value	Unit	
Melt Temperature	199 to 216	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

