SABIC® PPcompound 8611P

Polypropylene

Saudi Basic Industries Corporation (SABIC)

Message:

SABIC® PPcompound 8611P is a development grade, elastomer-modified mineral filled Polypropylene for automotive exterior applications. This material has been designed to combine a good stiffness and excellent impact performance with good processing and surface esthetics. This grade is UV stabilised and is suitable for painted applications also.

SABIC® PPcompound 8611P is a designated automotive grade.

General Information					
Filler / Reinforcement	Mineral filler				
Additive	Impact modifier				
	UV stabilizer				
Features	Impact modification				
	Rigid, good				
	Impact resistance, high				
	Good UV resistance				
	Workability, good				
	Sprayable				
Uses	Application in Automobile Field				
	Automotive exterior parts				
Forms	Particle				
Processing Method	Injection molding				
Physical	Nominal Value	Unit	Test Method		
Density	0.985	g/cm³	ISO 1183		
Melt Mass-Flow Rate (MFR) (230°C/2.16					
kg)	37	g/10 min	ISO 1133		
Molding Shrinkage (24 hr)	0.70 - 0.80	%	Internal method		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Stress (Yield, Injection Molded)	20.0	MPa	ISO 527-2/1A		
Tensile Strain (Break, Injection Molded)	80	%	ISO 527-2/1A		
Flexural Modulus ¹ (Injection Molded)	1650	МРа	ISO 178		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact			ISO 180/1A		
-20°C, injection molding	10	kJ/m²	ISO 180/1A		
0°C, injection molding	30	kJ/m²	ISO 180/1A		
23°C, injection molding	40	kJ/m²	ISO 180/1A		
Thermal	Nominal Value	Unit	Test Method		

Heat Deflection Temperature (1.8 MPa,					
Unannealed)	53.0	°C	ISO 75-2/A		
NOTE					
1.	Type 1A				

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

