KYOCERA XP-9003

Thermoset Polyester

KYOCERA Chemical Corporation

Message:

Utilizable in wide field. (miniaturization electronics parts, high reliability parts etc.) Features Excellent Dimensional Accuracy and Stability. (Possible to Shrinkage-less) Excellent Mechanical Characteristics. Excellent Electrical Characteristics. Excellent fluidity. (superior filling and molding) Possible to Mold by Low Pressure. Possible to Fast Cure in Low Temperature. For Compression molding, Injection molding and Transfer molding. Good metal corrosion properties and environmental friendly compounds. Because products do not use the halogen substances in flame retardant.

General Information			
Features	Environmentally Sound		
	Fast Cure		
	Good Dimensional Stability		
	Good Electrical Properties		
	Good Flow		
Uses	Electrical/Electronic Applications		
Forms	BMC - Bulk Molding Compound		
Processing Method	Compression Molding Injection Molding		
	Resin Transfer Molding		
Physical	Nominal Value	Unit	
Molding Shrinkage - Flow	0.0 to 0.050	%	
Water Absorption (Equilibrium)	< 0.10	%	
Mechanical	Nominal Value	Unit	
Flexural Strength	80.0 to 120	MPa	
Impact	Nominal Value	Unit	
Charpy Unnotched Impact Strength	15 to 25	kJ/m²	
Electrical	Nominal Value	Unit	Test Method
Arc Resistance	> 180	sec	
Insulation Resistance			
After Boiled	1.0E+9	ohms	
Normal Condition	1.0E+14	ohms	
Flammability	Nominal Value	Unit	Test Method
Flame Rating (1.60 mm)	V-0		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

