

Daelim Po1y® LD-62

Low Density Polyethylene
DAELIM INDUSTRIAL CO., LTD.

Message:

Daelim Po1y®LD-62 is a low density polyethylene product. It can be processed by extrusion coating or injection molding and is available in the Asia Pacific region. Daelim Po1y®LD-62 application areas include coating applications, film and food contact applications.

Features include:

- Strong adhesion
- Good processability
- odorless/tasteless channel

General Information	
Features	Workability, good Good adhesion Low shrinkage The smell is low to none
Uses	Films Laminate Coating application
Agency Ratings	ASTM D 1248, I, Class A, Cat. 3 FDA 21 CFR 177.1520
Forms	Particle
Processing Method	Extrusion coating Injection molding

Physical	Nominal Value	Unit	Test Method
Density	0.919	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	7.6	g/10 min	ASTM D1238

Additional Information			
Water vapor permeability, 25\$ - film, 38°C, 90%RH, ASTM E-96: 17 g/m² 24hTypical min coating weight: 9 g/m²Typical max neck-in: 3.0 cm			
Injection	Nominal Value	Unit	
Processing (Melt) Temp	280 - 320	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

