# Deco-Coat™ 60-7185

#### Acrylic

Epoxies, Etc.

#### Message:

UV 60-7185 is a one component, UV light curable, clear coating. 60-7185 is water clear and exhibits superior yellowing resistance. This product has been formulated to cure instantly when exposed to high intensity ultraviolet light. 60-7185 has excellent adhesion to a variety of substrates and is therefore suitable as an adhesive and coating candidate, or may be used in small potting applications.

UV 60-7185 may also be used as a decorative ultra clear doming resin on labels, pins, key fobs, magnets, etc... Its high gloss finish and outstanding clarity will enhance any image it is applied over.

Features:

Water Clear

One Part

Low Viscosity

Cures in seconds

100% solids (no solvents)

Low Shrinkage

General Information		
Features	Fast Cure	
	Good Adhesion	
	High Clarity	
	High Gloss	
	Low Viscosity	
Uses	Adhesives	
	Coating Applications	
	Decorative Parts	
	Labels	
Appearance	Clear/Transparent	
Processing Method	Encapsulating	
	Potting	
Uncured Properties	Nominal Value	Unit
Color	Clear/Transparent	
Solids Content	100	%
Density (25°C)	1.10	g/cm³
Viscosity (25°C)	0.80	Pa·s
Shelf Life	1	month
Cured Properties	Nominal Value	Unit
Shore Hardness (Shore A)	80 to 85	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

