CYCOLAC™ INP338T resin

Acrylonitrile Butadiene Styrene

SABIC Innovative Plastics

Message:

SABIC INP338T is an ultra high rubber ABS impact modifier resin, and is based on polybutadiene rubber. Offers superior impact efficiency, especially at low temperatures. Reduces notch sensitivity when alloyed with engineering polymers. Disperses easily. Provides abrasion and chemical resistance to polymers. Provides toughness to PVC sheet, profile, electrical conduit and injection molded applications. Increases the impact strength of recycle PVC and other recyclates. Can be blended with polyurethanes and other polymers for improved performance and economics. Can be used to improve the impact performance of PC, polyesters, and CPVC.

General Information			
Features	Impact resistance, high		
	Dispersible		
	Good wear resistance		
	Low temperature impact resistance		
	Good chemical resistance		
	Good toughness		
Uses	Additive		
RoHS Compliance	RoHS compliance		
Physical	Nominal Value	Unit	Test Method
Specific Gravity			
	0.948	g/cm³	ASTM D792
1	0.960	g/cm³	ISO 1183
Apparent Density	0.25	g/cm³	ASTM D1895
BD	70	%	Internal method
Mean Particle Size	200.0	μm	Internal method
Total NA Volatiles	0.20	%	Internal method
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	40		ASTM D2240
NOTE			
1.	Molded		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com No. 215, Lianhe North Road, Fengxian District, Shanghai, China

