EPAMOULD 760D15

Thermoplastic Polyurethane Elastomer (Polyether)

Epaflex Polyurethanes S.R.L.

Message:

The EPAMOULD 700 series includes products based on polyether. This allows polyurethanes which have excellent resistance to hydrolysis, resistance to microbial attack without the use of special additives, and good flexibility at very low temperatures.

General Information			
Additive	Beeswax		
Features	Flexibility at low temperatures		
	Antimicrobial		
	Hydrolysis resistance		
	Compliance of Food Exposure		
Physical	Nominal Value	Unit	
Density	1.17	g/cm³	
Hardness	Nominal Value	Unit	
Durometer Hardness (Shore D)	60		
Mechanical	Nominal Value	Unit	
Abrasion Loss	45.0	mm³	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

