

# MARPOL® Homo 3.5

Polypropylene Homopolymer

Marco Polo International, Inc.

## Message:

Additives: None

Recommended Applications: Stationery film, housewares, raffia/tapes/strapping, Also good for clear containers, opaque containers.

Homo 3.5 is a low flow polypropylene homopolymer resin available in pellet form. Homo 3.5 is often used in general injection molding or extrusion applications, and is mostfrequently sold into raffia markets.

General Information	
Features	Additive Free
	Homopolymer
	Low Flow
Uses	Containers
	Film
	Household Goods
	Stationary Supplies
	Strapping
	Tape
Processing Method	Extrusion
	Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.900	g/cm <sup>3</sup>	ASTM D792B
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.5	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	35.2	MPa	ASTM D638
Tensile Elongation (Yield)	11	%	ASTM D638
Flexural Modulus	1530	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	52	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

