Cheng Yu FRCV200

Polyamide 66

Cheng Yu Plastic Company Limited

Message:

Cheng Yu FRCV200 is a Polyamide 66 (Nylon 66) product filled with 30% mineral. It is available in Asia Pacific.

Characteristics include:

Flame Rated

Flame Retardant

High Stiffness

General Information			
Filler / Reinforcement	Mineral,30% Filler by Weight		
Features	Flame Retardant		
	High Stiffness		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.30	g/cm³	ASTM D792
Molding Shrinkage - Flow	0.20 to 2.0	%	ASTM D955
Water Absorption (24 hr)	1.0 to 2.0	%	ASTM D570
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (M-Scale)	90		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	88.3	MPa	ASTM D638
Flexural Strength	137	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	54	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (MPa, Unannealed)	0.45 255	°C	ASTM D648
Flammability	Nominal Value		Test Method
Flame Rating	V-1		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

