

ISOLOSS® LS-2000

Polyurethane
E-A-R Specialty Composites

Message:

ISOLOSS® LS-2000 is a Polyurethane material. It is available in North America.
Important attributes of ISOLOSS® LS-2000 are:
Chemical Resistant
Corrosion Resistant
Flame Retardant
Good Dimensional Stability
Good UV Resistance
Typical applications include:
Aerospace
Coating Applications
Engineering/Industrial Parts
Foam
Military Applications

General Information			
Features	Flame Retardant		
	Good Chemical Resistance		
	Good Corrosion Resistance		
	Good Dimensional Stability		
	Good UV Resistance		
	Ozone Resistant		
	Shock Absorbent		
	Vibration Damping		
Uses	Foam		
	Gaskets		
	Laminates		
	Seals		
Agency Ratings	AMS 3568		
	MIL P-1240C		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.320	g/cm ³	ASTM D792
Water Absorption (24 hr)	2.1	%	ASTM D570
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	1.19	MPa	ASTM D638
Tensile Elongation (Yield)	150	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method

Tear Strength	3.06	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-52.2	°C	ASTM D746
Thermal Conductivity	0.053	W/m/K	ASTM C177
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	1.3E+11	ohms·cm	ASTM D257
Dielectric Strength	2.2	kV/mm	ASTM D149

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT