

# PETILEN H2-26T

Low Density Polyethylene

PETKIM Petrokimya Holding A.S.

Message:

Application: Food packing

General Information			
Uses	Food Packaging		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.923 to 0.929	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.5 to 2.5	g/10 min	ASTM D1238
Optical	Nominal Value	Unit	Test Method
Gloss	61		ASTM D2457
Haze	7.1	%	ASTM D1003
Additional Information	Nominal Value	Test Method	
Film Quality <sup>1</sup>	A	Internal Method	
NOTE			
1.	ALKATHENE 36		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

