SILVER® SA-5304

Polyolefin

Guangdong Silver Age Sci & Tech. Co., Ltd

Message:

SILVER® SA-5300 is low—smoke halogen-free flame retardant compound for cable which is polyolefin based material containing inorganic flame retardant, antioxidant,lubricant, etc. It is non-halogen, non-heavy metal, can pass RoHS. The series compound which can be radiation cross—linking makes it higher performance for temperature—resistant, better mechanical property and better insulating property. It can be used for power—cable, the cable for metro, and the cable for nuclear power plant, and so on. Low Smoke Zero Halogen Flame Retardant Polyolefin Series Thermoplastic Series Characteristics:

low smoke zero halogen

Applications:

wire and cable, plug, electronic line and so on

General Information			
Additive	Antioxidant		
	Flame Retardant		
	Lubricant		
Features	Antioxidant		
	Flame Retardant		
	Halogen Free		
	Low Smoke Emission		
	Lubricated		
Uses	Electrical Parts		
	Electrical/Electronic Applications		
	Nuclear Power Applications		
	Plugs		
	Wire & Cable Applications		
RoHS Compliance	RoHS Compliant		
Physical	Nominal Value	Unit	
Specific Gravity	1.50	g/cm³	
рН	6.2		
Hot Pressure Test (80°C)	< 50	%	
Halogenidric Acid Emissions	2.70	mg/g	
Smoke Density			
Flame	59		
Non-flame	190		
Toxicity	0.800		
Electrical Conductivity	2.40	μS/mm	

Hardness	Nominal Value	Unit
Durometer Hardness		
Shore A	88	
Shore D	40	
Mechanical	Nominal Value	Unit
Tensile Strength	9.80	MPa
Tensile Elongation (Break)	270	%
Aging	Nominal Value	Unit
Change in Tensile Strength (100°C, 168 hr)	21	%
Change in Ultimate Elongation (100°C, 168		
hr)	-14	%
Electrical	Nominal Value	Unit
Volume Resistivity	8.0E+13	ohms∙cm
Dielectric Strength	27	kV/mm
Flammability	Nominal Value	Unit
Oxygen Index	43	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

