Elvax® 240W

Ethylene Vinyl Acetate Copolymer

DuPont Packaging & Industrial Polymers

Message:

DuPont[™] Elvax[®] 240W is an ethylene-vinyl acetate copolymer resin for use in industrial applications. This resin is supplied in pellet form and contains a "W" amide additive to improve pellet handling.

Composition

28 % By Weight Vinyl Acetate comonomer content

Contains a "W" amide additive to improve pellet handling.

Thermal Stabilizer: BHT antioxidant

Applications

Elvax[®] resins can be used in a variety of applications involving molding, compounding, extrusion, adhesives, sealants, and wax blends. For additional information and properties associated with specific applications, please refer to the Grade Selector Guides found on the Elvax[®] website for industial applications. http://www2.dupont.com/Elvax/en_US/tech_info/index.html

General Information					
Additive	Antioxidant				
	Heat Stabilizer				
	Unspecified Additive				
Features	Antioxidant				
	Copolymer				
	Food Contact Acceptable				
	Heat Stabilized				
Uses	Adhesives				
	Blending				
	Compounding				
	Industrial Applications				
	Sealants				
	Wire Jacketing				
Agency Ratings	FDA 21 CFR 177.1350(a)(1)				
Forms	Pellets				
Processing Method	Blow Molding				
	Compounding				
	Compression Molding				
	Extrusion				
	Injection Molding				
	Sheet Extrusion				
	Structural Foam Molding				
Physical	Nominal Value	Unit	Test Method		

Specific Gravity	0.951	g/cm³	ASTM D792, ISO 1183		
Melt Mass-Flow Rate (MFR) (190°C/2.16					
kg)	43	g/10 min	ASTM D1238, ISO 1133		
Vinyl Acetate Content	28.0	wt%			
Thermal	Nominal Value	Unit	Test Method		
Vicat Softening Temperature	40.0	°C	ASTM D1525, ISO 306		
Peak Melting Temperature	74.0	°C	ASTM D3418, ISO 3146		
Additional Information	Nominal Value	Unit			
Processing Temperature	< 230	°C			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

