

Hanwha Total PP EB130

High Melt Strength Polypropylene
HANWHA TOTAL PETROCHEMICALS Co., Ltd.

Message:

EB130 is a polypropylene compound featuring high melt strength, processability. EB130 displays superior impact strength, with excellent formability during vacuum forming, compression molding.

General Information	
Features	Good Melt Strength Good Processability High Impact Resistance
Uses	Automotive Exterior Parts Blow Molding Applications
Forms	Pellets
Processing Method	Blow Molding Compression Molding Vacuum Forming

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.910	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	0.60	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	26.5	MPa	ASTM D638
Tensile Elongation (Break)	400	%	ASTM D638
Flexural Modulus	932	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
0°C	69	J/m	
23°C	No Break		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

