Manner Flexible PVC X3653

Flexible Polyvinyl Chloride

Manner Plastics, L.P.

Message:

General purpose tubing, profile extrusion and injection molding.

General Information			
Features	General Purpose		
Uses	Profiles		
Processing Method	Extrusion		
	Injection Molding		
	Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.37 to 1.41	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	75		
Shore A, 15 sec	74		
Mechanical	Nominal Value	Unit	Test Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

MPa

MPa

ASTM D638

ASTM D638

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

11.0

5.17

330

Tel: +86 21 5895 8519

Tensile Strength

100% Strain, 1.52 mm

Tensile Elongation (Break, 1.52 mm)

1.52 mm

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

