SolVin 267RC

Polyvinyl Chloride

INOVYN

Message:

Polyvinyl chloride made by suspension polymerisation. APPLICATIONS

Sewage pipes, pressure pipes, rigid profiles, window frames, electrical ducts

General Information			
Features	Suspension Polymers		
Uses	Conduit		
	General Purpose		
	Piping		
	Profiles		
	Windows & Doors		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.58	g/cm³	ISO 60
K-Value	67.0		ISO 1628-2
Sieve Analysis			ISO 1624
Retained on 0.063 mm sieve	> 95	%	
Retained on 0.250 mm sieve	< 5.0	%	
Volatile Matter	< 0.30	%	ISO 1269
Residual Vinyl Chloride Monomer	< 1	ppm	ISO 6401

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

