# Geon™ Vinyl Flexible 90252

#### Flexible Polyvinyl Chloride

PolyOne Corporation

#### Message:

Geon™ Vinyl Flexible 90252 is a Flexible Polyvinyl Chloride product. It can be processed by extrusion or injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Applications of Geon™ Vinyl Flexible 90252 include automotive, coating applications, engineering/industrial parts and sealing applications.

General Information			
Features	General Purpose		
Uses	Automotive Applications		
	Gaskets		
	General Purpose		
	Protective Coverings		
	Seals		
Forms	Pellets		
Processing Method	Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.30	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	88		
Shore A, 15 sec	80		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength <sup>1</sup>			ASTM D638
Break	16.6	MPa	
100% Strain	7.90	MPa	
Tensile Elongation <sup>2</sup> (Break)	400	%	ASTM D638
Tear Resistance <sup>3</sup>	64.0	kN/m	ASTM D1004
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-32.0	°C	ASTM D746
NOTE			
1.	Type IV, 510 mm/min		
2.	Type IV, 510 mm/min		
3.	Die C, 2 in/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

