

Formolon® 113

Polyvinyl Chloride Copolymer

Formosa Plastics Corporation, U.S.A.

Message:

F-113 has been developed primarily to meet the processing requirements of the vinyl composition tile (VCT) manufacturers. In addition to vinyl floor tile industry, F-113 has found success in protective and strippable coatings.

General Information			
Features	Copolymer		
Uses	Coating Applications		
	Flooring		
Agency Ratings	EC 1907/2006 (REACH)		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.56	g/cm ³	ASTM D1895A
K-Value	48.0		
Vinyl Acetate Content	13.0	wt%	
Inherent Viscosity	0.48		ASTM D1243
Relative Viscosity	1.55		
Sieve Analysis ¹	100	%	ASTM D1921
Volatiles	0.30	%	
NOTE			
1.	Through 40 Mesh Screen, Method B		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT