

INTOL® 1783

Emulsion Styrene Butadiene Rubber

Versalis S.p.A.

Message:

Intol® 1783 is an emulsion styrene-butadiene rubber obtained by cold polymerisation using a mixture of rosin acid and fatty acid soaps as emulsifiers.

It is made at the Hythe production facility in UK.

It is a medium bound styrene copolymer extended with RAE oil.

Key Features

E-SBR is a general purpose rubber characterised by good processability, mechanical properties and abrasion resistance.

It has a limited resistance to oil and weather but properly compounded, it is suitable for use in outdoor applications.

Intol® 1783 is the RAE oil extended alternative to Intol® /Europrene® 1712.

Main Applications

Tyre manufacturing and retreading, conveyor belts, hoses and other mechanical goods.

General Information			
Features	Copolymer		
	General Purpose		
	Good Abrasion Resistance		
	Good Processability		
Uses	Belts/Belt Repair		
	Conveyor Parts		
	General Purpose		
	Hose		
	Tire Repair		
Forms	Bale		
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity (ML 1+4, 100°C)	50	MU	ASTM D1646
Bound Styrene	23.5	%	ASTM D5775
Oil Type (TRAE Oil)	37.5	phr	ASTM D5774
Ash Content	< 0.5	wt%	ASTM D5667
Organic Acid	5.0	wt%	ASTM D5774
Soap	< 0.4	wt%	ASTM D5774
Volatile Matter	< 0.75	wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

