

ICORENE® 1761 V2 White 1801

Metallocene Medium Density Polyethylene

ICO Polymers EMEA, A Division of A. Schulman

Message:

ICORENE® 1761 V2 White 1801 is a medium density metallocene polyethylene containing a flame retardant additive package for rotational moulding applications.

This grade has been tested by Schulman R&D comply with the requirements to meet UL94 V2 at 3mm thickness.

General Information			
Additive	Flame Retardant 1		
Features	Flame Retardant		
	Good UV Resistance		
Uses	General Purpose		
	Tanks		
Appearance	White		
Forms	Powder		
Processing Method	Rotational Molding		
Physical	Nominal Value	Unit	Test Method
Density	> 1.00	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	5.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	17.0	MPa	ASTM D638
Tensile Elongation (Break)	650	%	ASTM D638
Flexural Modulus	500	MPa	ASTM D790
Flammability	Nominal Value	Test Method	
Flame Rating (3.00 mm)	V-2	Internal Method	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT