

# YUCLAIR® DX900

Medium Density Polyethylene

SK Global Chemical

Message:

YUCLAIR® DX900 is a Medium Density Polyethylene product. It is available in Asia Pacific, Europe, or North America. Typical application: Plumbing/Piping/Potable Water. Primary characteristic: good processability.

General Information			
Features	Good Processability		
Uses	Piping		
Physical	Nominal Value	Unit	Test Method
Density	0.936	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.61	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Tensile Strength - MD			ASTM D882
Yield	16.2	MPa	
Break	40.2	MPa	
Tensile Elongation - MD (Break)	800	%	ASTM D882

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT