

Daelim Po1y® LH-58120UV

High Density Polyethylene
DAELIM INDUSTRIAL CO., LTD.

Message:

Daelim Po1y®LH-58120UV is a high density polyethylene product. It can be processed by injection molding and is available in the Asia-Pacific region. Typical application areas are: food contact applications.

Features include:

- high gloss
- Good stiffness
- good weather resistance

General Information			
Features	Rigid, good		
	Highlight		
	Good liquidity		
	Good weather resistance		
Agency Ratings	ASTM D 1248, IV, Class A, Cat. 2		
	FDA 21 CFR 177.1520		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density	0.958	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	11	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	28.4	MPa	ASTM D638
Tensile Elongation ² (Break)	900	%	ASTM D638
Flexural Modulus	1420	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	59	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-118	°C	ASTM D746
Additional Information			
Ultimate Elongation, ASTM D-638, Type VI Spec, 50 mm/min: >900%Brittle Temperature, ASTM D-746: <-118°C			
Injection	Nominal Value	Unit	
Processing (Melt) Temp	200 - 260	°C	
NOTE			
1.	50 mm/min		
2.	50 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

