

Paracril OZO® SP90

Polyvinyl Chloride + NBR

INSA

Message:

Description:

Pre-fluxed blend of 60 nbr / 40 pvc / 70 dop

Easy processing

Excellent abrasion resistant

Good ozone resistance

Applications:

Low durometer roll covers

General Information			
Features	Good Abrasion Resistance		
	Good Processability		
	Ozone Resistant		
Uses		Protective Coverings	
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.06	g/cm ³	ASTM D297
Mooney Viscosity (ML 1+4, 100°C)	16 to 26	MU	ASTM D1646
Ash Content	< 0.8	wt%	ASTM D5667
Volatile Matter	< 0.75	wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT