

# Nipoflex® 750

Ethylene Vinyl Acetate Copolymer

TOSOH Corporation

## Message:

Nipoflex® 750 is an Ethylene Vinyl Acetate Copolymer (EVA) material. It is available in Asia Pacific, Europe, or North America for blown film, foam processing, injection molding, or sheet extrusion.

Important attributes of Nipoflex® 750 are:

- Clarity
- Copolymer
- Good Flexibility
- Good Weather Resistance
- High ESCR (Stress Crack Resistant)

Typical applications include:

- Caps/Lids/Closures
- Consumer Goods
- Film
- Labels

General Information	
Features	Copolymer
	Good Flexibility
	Good Weather Resistance
	High Clarity
	High Elasticity
	High ESCR (Stress Crack Resist.)
	High Gloss
	High Impact Resistance
Uses	Closures
	Film
	Labels
	Lids
	Toys
Forms	Pellets
Processing Method	Blown Film
	Foam Processing
	Injection Molding
	Sheet Extrusion

Physical	Nominal Value	Unit	Test Method
Density	0.953	g/cm <sup>3</sup>	ASTM D1505
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	66.0	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

