Moplen EP300L

Polypropylene Copolymer

PolyMirae

Message:

Moplen EP300L is the polypropylene block copolymer manufactured by PMC under the license of BASELL using the Spheripol process. Moplen EP300L is a block copolymer selected by customers for use in injection molding of toys, crates, battery case.

Moplen EP300L resin meets the FDA requirements in the Code of Federal Regulations in 21 CFR 177.1520 for food contact.

Moplen EP300L has a flame rating of UL94HB.

General Information					
UL YellowCard	E215205-229286				
Features	Block Copolymer				
	Food Contact Acceptable				
	Good Stiffness				
	Good Toughness				
	Low Temperature Impact Resistance				
	Low Warpage				
Uses	Battery Cases				
	Crates				
	Pails				
	Toys				
Agency Ratings	FDA 21 CFR 177.1520				
RoHS Compliance	Contact Manufacturer				
Forms	Pellets				
Processing Method	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Density	0.900	g/cm³	ASTM D1505		
Melt Mass-Flow Rate (MFR) (230°C/2.16					
kg)	5.0	g/10 min	ASTM D1238		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	90		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield, Injection Molded)	25.5	MPa	ASTM D638		
Tensile Elongation (Yield, Injection Molded)	6.0	%	ASTM D638		
Flexural Modulus (Injection Molded)	1030	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact			ASTM D256		
-20°C	79	J/m			
23°C	490	J/m			

Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45			
MPa, Unannealed, Injection Molded)	90.0	°C	ASTM D648
Vicat Softening Temperature	150	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

