Roscom PVC 600-95/96

Flexible Polyvinyl Chloride

Roscom, Inc.

Message:

ROSCOM PVC 600-95/96 is an economically formulated flexible vinyl compound designed for both extrusion and injection molding. This compound features excellent heat stability and lubrication for trouble-free, consistent processing. Typical applications range from extension cord plugs to extruded weatherstripping and other general purpose applications.

General Information			
Features	Good Flexibility		
	Good Processability		
	Good Thermal Stability		
	Lubricated		
Uses	General Purpose		
	Weatherstripping		
Processing Method	Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.42 to 1.48	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	92 to 98		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	20.8	MPa	ASTM D412
Tensile Strength (Yield)	22.7	MPa	ASTM D412
Tensile Elongation (Break)	160	%	ASTM D412
Tear Strength ¹	142	kN/m	ASTM D624
NOTE			
1.	Die C		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

