

Evermore PUR SC-636HR

Polyurethane

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR SC-636HR is a Polyurethane product. It can be processed by spraying and is available in Asia Pacific. Applications of Evermore PUR SC-636HR include adhesives/tapes and coating applications. Primary characteristic: good adhesion.

General Information			
Features	Cleanable		
	Good Adhesion		
Uses	Adhesives		
	Coating Applications		
Processing Method	Spraying		
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	0.177 to 0.275	MPa	ASTM D412
Fill Analysis	Nominal Value	Unit	Test Method
Melt Viscosity (25.0°C)	0.300 to 0.500	Pa·s	ASTM D3835
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	56 to 60	%	
Solvents	Eac, MEK		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

