

Peripor® 200 E

Expanded Polystyrene

BASF Corporation

Message:

Application

For the production of moldings primarily in the high bulk density range for applications involving stresses due to compression and moisture.

Fire characteristics in conformity with:

DIN 4102 - B1 (flame-retardant)

EN ISO 13501-1-E

Product description

Expandable polystyrene (EPS) with uniformly distributed flame retardant (blowing agent: pentane)

For additional information pertaining to the fire behavior please contact the local BASF representative.

General Information		
Additive	Blowing Agent 2	
	Flame Retardant	
Features	Flame Retardant	
Uses	Foam	
	Insulation	
Agency Ratings	DIN 4102/B1	
	EC 1907/2006 (REACH)	
Forms	Spheres	
Physical	Nominal Value	Unit
Apparent Density	0.03 to 0.04	g/cm ³
Sieve Analysis		
< 800.0 µm	< 4.0	%
0.800 to 2.00 mm	> 94	%
> 2.50 mm	< 2.0	%
Aging - intermediate	0.4 to 2.0	day
Bead Size	1.00 to 2.30	mm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

