

# Aropol™ L 2450

Thermoset Polyester

Ashland Performance Materials

Message:

Ashland Resins for the Pultrusion Market  
Chemistry  
High reactivity UPR  
Performance Attributes  
Excellent physical properties. Good weathering.  
Typical Applications  
Rigid, thin walled parts.

General Information		
Features	Good Weather Resistance	
	High Reactivity	
	High Rigidity	
Uses	Thin-walled Parts	
Processing Method	Pultrusion	
Physical	Nominal Value	Unit
Solution Viscosity	2400	mPa · s
Mechanical	Nominal Value	Unit
Tensile Modulus	3930	MPa
Tensile Strength	58.6	MPa
Tensile Elongation (Break)	1.8	%
Flexural Modulus	4000	MPa
Flexural Strength	88.3	MPa
Thermal	Nominal Value	Unit
Heat Deflection Temperature	138	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT