Delrin® Stock Shapes 527UV

Acetal (POM) Homopolymer

Ensinger Inc.

Message:

THIS MATERIAL REPLACES DELRIN 507 WHICH HAS BEEN DISCONTINUED BY DuPont.

Delrin® 527UV BK701 is a black homopolymer acetal that has been enhanced with UV stabilizers. It is also available in natural on a custom run basis. Developed by DuPont to replace Delrin® 507, this material is particularly suited to automotive and other outdoor applications. It exhibits improvements in UV aging characteristics and thermal stability.

DELRIN® 527UV BK is typically used for applications exposed to the outdoors in such industries as electronics, communications, transportation, construction and marine.

General Information					
Additive	UV stabilizer				
Features	Homopolymer				
	Good UV resistance				
	Machinable				
	High hardness				
Uses	Ship application				
	Electrical/Electronic Applications				
	Architectural application field				
	Application in Automobile Field				
	Outdoor application				
	Communication application				
Appearance	Black				
	Natural color				
Forms	Shapes				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.41	g/cm³	ASTM D792		
Water Absorption (24 hr)	0.14	%	ASTM D570		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness			ASTM D785		
Class m	92		ASTM D785		
Class r	118		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Modulus	2970	MPa	ASTM D638		
Tensile Strength (Yield)	71.0	MPa	ASTM D638		
Tensile Elongation (Break)	16	%	ASTM D638		
Flexural Modulus	4030	MPa	ASTM D790		
Flexural Strength	117	MPa	ASTM D790		

Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	68	J/m	ASTM D256
Additional Information			

Data obtained from extruded shapes material.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

