

ICORENE® 6152 OSF

Linear Low Density Polyethylene

ICO Polymers EMEA, A Division of A. Schulman

Message:

ICORENE® 6152 OSF is a linear low density polyethylene especially formulated with a foaming agent suitable for rotomoulding. This product has been developed for the foam filling of structural rotational mouldings.

ICORENE® 6152 OSF is intended to be used with an appropriate ICORENE® skin material in a one shot moulding process.

(ICORENE® Kcel152)

General Information			
Uses	Containers		
	Lids		
	Water Sports Equipment		
Forms	Pellets		
Processing Method	Rotational Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.936	g/cm ³	ASTM D1505
Apparent Density ¹	0.11 to 0.15	g/cm ³	Internal Method
NOTE			
1.	ICO R&D; test		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

