

SEQUEL® 1493-UV NH533

Polypropylene

LyondellBasell Industries

Message:

Sequel 1493-UV NH533 thermoplastic polyolefin material is typically used for large exterior automotive applications requiring a balance of stiffness and impact resistance, as well as excellent processability.

General Information		
Features	Rigid, good	
	Impact resistance, good	
	Workability, good	
Uses	Car anti-collision bar	
	Application in Automobile Field	
	Automotive exterior parts	
Processing Method	Injection molding	
Physical	Nominal Value	Unit
Density (23°C)	0.950	g/cm ³
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	26	g/10 min
Mechanical	Nominal Value	Unit
Tensile Strength ¹ (Yield, 23°C)	19.0	MPa
Flexural Modulus ² (23°C)	1350	MPa
NOTE		
1.	50 mm/min	
2.	2.0 mm/min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT