

# INNOBATCH® PPH 3160

Polypropylene Homopolymer

Inno-Comp Ltd.

## Message:

INNOBATCH® PPH 3160 is a 60% talc-filled polypropylene homopolymer based masterbatch. This grade is available in nature coloured form.

General Information			
Filler / Reinforcement	Talc,60% Filler by Weight		
Features	Homopolymer		
Uses	Appliances		
	Furniture		
	Masterbatch		
	Packaging		
Appearance	Natural Color		
Resin ID (ISO 1043)	PP-H TD60		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	1.50	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	12	g/10 min	ISO 1133
Ash Content (600°C)	53 to 63	%	ISO 3451-1A
Injection	Nominal Value	Unit	
Drying Temperature	80.0	°C	
Drying Time	2.0	hr	
Suggested Max Moisture	0.070	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

