

Daelim Po1y® 5502

High Density Polyethylene
DAELIM INDUSTRIAL CO., LTD.

Message:

Daelim Po1y® 5502 is a High Density Polyethylene product. It can be processed by blow molding and is available in Asia Pacific. Applications of Daelim Po1y® 5502 include food contact applications, bottles, consumer goods and household applications.

Characteristics include:

- Good Processability
- Good Stiffness
- Impact Resistant

General Information			
Features	Good Impact Resistance		
	Good Processability		
	Good Stiffness		
Uses	Bottles		
	Cosmetics		
	Household Goods		
	Non-specific Food Applications		
Agency Ratings	ASTM D 1248, II, Class A, Cat. 5		
	FDA 21 CFR 177.1520		
Forms	Pellets		
Processing Method	Blow Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.955	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.35	g/10 min	ASTM D1238
Environmental Stress-Cracking Resistance (F50)	30.0	hr	ASTM D1693B
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	27.5	MPa	ASTM D638
Tensile Elongation (Break)	> 600	%	ASTM D638
Flexural Modulus	1180	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (-20°C)	340	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	< -76.0	°C	ASTM D746
Injection	Nominal Value	Unit	
Processing (Melt) Temp	180 to 200	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

