

NEFTEKHIM PE 4223T (23407)

Linear Low Density Polyethylene

Nizhnekamskneftekhim Inc.

Message:

Product obtained by gas phase polymerization of ethylene in presence of complex metalorganic catalysts.
Stabilization recipe: antacid, antioxidant, thermostabilizer, dispersing agent..
Application: extrusion coating general purpose grade, blending.
Technical requirements: TU 2211-145-05766801-2008

| General Information | | | |
|---|--|--------------------|-------------|
| Additive | Acid Neutralizer | | |
| | Antioxidant | | |
| | Heat Stabilizer | | |
| Features | Acid Resistant | | |
| | Antioxidant | | |
| | Dispersible | | |
| | Heat Stabilized | | |
| Uses | Blending | | |
| | Coating Applications | | |
| | General Purpose | | |
| Forms | Pellets | | |
| Processing Method | Extrusion Coating | | |
| Physical | Nominal Value | Unit | Test Method |
| Density | 0.921 to 0.925 | g/cm ³ | ASTM D1505 |
| Melt Mass-Flow Rate (MFR) (190°C/2.16 kg) | 6.0 to 8.0 | g/10 min | ASTM D1238 |
| Gel Content ¹ | 100 | pcs/m ² | |
| Melt Flow Ratio - MFR 21.6 kg/MFR 2.16 kg | < 30.0 | | ASTM D1238 |
| NOTE | | | |
| 1. | p.6 attachment A TU 2211-145-05766801 | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

