

Jampilen HP456H

Polypropylene Homopolymer

Jam Polypropylene Company

Message:

Jampilen HP456H is a homopolymer, suitable for extrusion and thermoforming applications. It is formulated with a low water-carry-over additive package. Typical applications of Jampilen HP456H are strapping, monofilaments and tapes. Jampilen HP456H has a wide range of approval for contact with food.

General Information	
Features	Food Contact Acceptable
	Good Stretchability
	Homopolymer
	Low Water Carryover
Uses	Agricultural Applications
	Geo Membranes
	Strapping
	Tape
	Textile Applications
Processing Method	Extrusion
	Filament Extrusion
	Thermoforming

Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	1.8	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	1500	MPa	ISO 527-2/1
Tensile Stress (Yield)	34.0	MPa	ISO 527-2/50
Tensile Strain			ISO 527-2/50
Yield	11	%	
Break	> 50	%	
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	97.0	°C	ISO 75-2/B
Vicat Softening Temperature	154	°C	ISO 306/A50

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

