

Karina WHITE PVC COMPOUND

851-10/127-Y-ERYB-AS-PO

Polyvinyl Chloride

Karina Ind. e Com. de Plásticos Ltda

Message:

WEATHER RESISTANT PVC COMPOUND IN POWDER FORM RECOMMENDED FOR EXTRUSION IN TWIN SCREW EXTRUDER OF WINDOW AND DOOR PROFILES.

General Information			
Features	Good Weather Resistance		
Uses	Profiles		
	Windows & Doors		
Appearance	White		
Forms	Powder		
Processing Method	Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.45 to 1.51	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 15 sec)	78 to 82		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	> 39.2	MPa	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT