

ExxonMobil™ LDPE LD 258

Low Density Polyethylene Resin

ExxonMobil Chemical

Message:

LD 258 is a low density polyethylene extrusion coating grade, which has better sensory properties than existing low odor/odorless low density polyethylene extrusion coating polymers. The development of LD 258 reflects our in-depth understanding of the influence of extrusion coating process parameters and resin properties on the final odorless and odorless properties of coating materials.

General Information			
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	8.2	g/10 min	ASTM D1238
Legal statement			

有关潜在食品接触应用合规信息(例如:FDA,EU,HPFB),请与埃克森美孚化工客户服务代表联系.本产品不宜在医疗应用中使用,亦不应在任何此类应用中使用

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT