

ICORENE® N6603

Acrylonitrile Butadiene Styrene

ICO Polymers EMEA, A Division of A. Schulman

Message:

ICORENE® N6603 is premium quality high flow ABS grade suitable for general purpose use. It is supplied in powder form typically for processes such as masterbatch production.

General Information			
Features	High Flow		
	High Impact Resistance		
Uses	Compounding		
	Masterbatch		
Forms	Powder		
Physical	Nominal Value	Unit	Test Method
Density	1.04	g/cm ³	ISO 1183
Melt Volume-Flow Rate (MVR) (220°C/10.0 kg)	34.0	cm ³ /10min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	33.0	MPa	ISO 527-2/50
Flexural Stress ¹	65.0	MPa	ISO 178
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature ²	95.0	°C	ISO 306/B50
NOTE			
1.	2.0 mm/min		
2.	Oil		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT