

PIVINEL™ 116-NRS

Polyvinyl Chloride + NBR

HELLENIC CABLES S.A.

Message:

Description: PVC/NBR based compound

Packaging: In PE bags of 25 kg or in big bags of approximately 1000 kg.

Use: Production of elastic profile for tightness in fridges etc.

General Information		
Uses	Profiles	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Specific Gravity	1.25	g/cm ³
Extrusion	Nominal Value	Unit
Cylinder Zone 1 Temp.	150	°C
Cylinder Zone 2 Temp.	160	°C
Cylinder Zone 3 Temp.	165	°C
Cylinder Zone 4 Temp.	170	°C
Cylinder Zone 5 Temp.	170	°C
Cylinder Zone 6 Temp.	170	°C
Cylinder Zone 7 Temp.	175	°C
Cylinder Zone 8 Temp.	175	°C
Cylinder Zone 9 Temp.	175	°C
Head Temperature	175	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT