

Pro-fax Ultra SC973X

Polypropylene Impact Copolymer

LyondellBasell Industries

Message:

Pro-fax Ultra SC973X high melt flow impact polypropylene copolymer is available in pellet form. This resin is typically used in thin-wall injection molding applications and offers excellent stiffness and good antistatic properties.

For regulatory compliance information see Pro-fax Ultra SC973X Product Stewardship Bulletin (PSB).

General Information			
Additive	Antistatic		
	Nucleating Agent		
Features	Antistatic		
	Good Stiffness		
	High Flow		
	Impact Copolymer		
	Nucleated		
Uses	Containers		
	Food Containers		
	Thin-walled Containers		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.898	g/cm ³	ASTM D792B
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	110	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	28.0	MPa	ASTM D638
Tensile Elongation (Yield)	5.0	%	ASTM D638
Flexural Modulus - 1% Secant ²	1490	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	32	J/m	ASTM D256A
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	116	°C	ASTM D648
NOTE			
1.	50 mm/min		
2.	1.3 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

