

# Viton® B-600

Fluoroelastomer  
DuPont Performance Elastomers

Message:

Viton® B- 600 is a fluororubber (Fluorelastomer) product. It can be processed by coating or compression molding and is available in North America or Europe. Viton® B- 600 applications include hoses, engineering/industrial accessories, glue/gummed paper, sealing applications and food contact applications.  
Features include:  
accessible food  
chemical resistance  
Medium viscosity

General Information	
Features	Solvent resistance
	Compliance of Food Exposure
	Medium viscosity
Uses	Washer
	Pipe
	Pipe fittings
	Metal bonding
	Seals
	Coating application
Agency Ratings	FDA 21 CFR 177.2600 2
Forms	Particle
Processing Method	Coating
	Compression molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.86	g/cm <sup>3</sup>	ASTM D792
Elastomers	Nominal Value	Unit	Test Method
Compression Set (200°C, 70 hr)	22	%	ASTM D395

Additional Information			
Nominal Viscosity, ML 1 + 10, 121°C: 60Polymer Fluorine Content: 68.5%			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

