

# EnviroPro 2515GM

Polypropylene Copolymer

West Michigan Compounding

## Message:

EnviroPro 2515GM is a polypropylene copolymer (PP Copoly) product, which contains glass/mineral filler. It is available in North America. Typical application areas are: automotive industry.

Features include:

High stiffness

Copolymer

anti-warping

General Information			
Filler / Reinforcement	Glass \Mineral		
Features	Low warpage		
	Rigidity, high		
	Copolymer		
Uses	Application in Automobile Field		
Appearance	Black		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.16	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	5.0	g/10 min	ASTM D1238
Molding Shrinkage - Flow	0.40	%	ASTM D955
Ash Content	30	%	ASTM D5630
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	52.9	MPa	ASTM D638
Tensile Elongation (Break)	6.0	%	ASTM D638
Flexural Modulus	3450	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	160	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	148	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

