# Jampilen HP510L

### Polypropylene Homopolymer

#### Jam Polypropylene Company

#### Message:

Jampilen HP510L is a polypropylene homopolymer with good flow properties and is particularly suitable for the extrusion of film yarn, monofilament, cast film and sheet. Jampilen HP510L combines outstanding processability with good mechanical properties. Film yarn of Jampilen HP510L is used for baler twines, packaging twines and ropes. Jampilen HP510L is well suited for the production of monofilament used for instance in brush and broom filling and technical applications.

General Information				
Features	Good Flow			
	Good Processability			
	Homopolymer			
Uses	Drinking Straws			
	Filaments			
	Film			
	Packaging			
	Rope			
	Sheet			
	Stationary Supplies			
	Twine			
Processing Method	Cast Film			
	Filament Extrusion			
	Film Extrusion			
	Sheet Extrusion			
Physical	Nominal Value	Unit	Test Method	
Density	0.900	g/cm³	ASTM D1505	
Melt Mass-Flow Rate (MFR) (230°C/2.16				
kg)	6.5	g/10 min	ASTM D1238	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	100		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	35.0	MPa	ASTM D638	
Tensile Elongation (Yield)	12	%	ASTM D638	
Flexural Modulus	1500	МРа	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (23°C)	40	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	

Deflection Temperature Under Load (0.4	45		
MPa, Unannealed)	94.0	°C	ASTM D648
Vicat Softening Temperature	154	°C	ASTM D1525 <sup>1</sup>
Accelerated Oven Ageing (150°C)	360	hr	ASTM D3012
NOTE			
1.	Loading 1 (10 N)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

