

# Pujie CPE130A

Chlorinated Polyethylene

Zhanhua Pujie Chemical Technology Co.,Ltd

## Message:

CM30,High molecular weight, superior mechanical performance, high modules, low chlorine content, excellent low temperature property, excellent absorption ability to filler.

General Information		
Features	Rigidity, high	
	High molecular weight	
	Low temperature resistance	
Uses	Industrial application	
	Pipe	
	Application in Automobile Field	
Physical	Nominal Value	Unit
Apparent Density	> 0.50	g/cm <sup>3</sup>
Mooney Viscosity (ML 1+4, 125°C)	80 - 100	MU
Chlorine Content	29.0 - 31.0	wt%
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A)	< 60	
Mechanical	Nominal Value	Unit
Tensile Strength	> 8.50	MPa
Tensile Elongation (Break)	> 700	%
Thermal	Nominal Value	Unit
Heat of Fusion		J/g
Impurities		pcs/50 g
Volatiles		%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT