Lotryl® 35BA320

Ethylene Butyl Acrylate Copolymer

Arkema

Message:

1.

LOTRYL® 35BA320 is a random copolymer of Ethylene and Butyl Acrylate produced by high-pressure radicalar polymerization process. Applications

Due to the high butyl acrylate content, LOTRYL® 35BA320 can be used for applications where flexibility and polarity are required. Combined with a high fluidity, LOTRYL® 35BA320 is particularly recommended for the formulation of hot melt adhesives. It can also be used as processing-aid in highly filled compounds.

Good Flexibility		
Random Copolymer		
Adhesives		
Plastics Modification		
Nominal Value	Unit	Test Method
0.930	g/cm³	ISO 1183, ASTM D1505
260 to 350	g/10 min	ASTM D1238, ISO 1133
33.0 to 37.0	wt%	
Nominal Value	Unit	Test Method
52		ASTM D2240, ISO 868
Nominal Value	Unit	Test Method
2.00	MPa	ASTM D638, ISO 527-2
200	%	ASTM D638, ISO 527-2
Nominal Value	Unit	Test Method
< 40.0	°C	ISO 306/A, ASTM D1525 ¹
65.0	°C	ISO 11357-3
85	°C	ASTM E28
Nominal Value	Unit	
150 to 170	°C	
170	°C	
170	°C	
170	°C	
170	°C	
	Random Copolymer Adhesives Plastics Modification Nominal Value 0.930 260 to 350 33.0 to 37.0 Nominal Value 52 Nominal Value 2.00 200 Nominal Value < 40.0 65.0 85 Nominal Value 150 to 170 170 170 170	Random Copolymer Adhesives Plastics Modification Nominal Value Unit 0.930 g/cm³ 260 to 350 g/10 min 33.0 to 37.0 wt% Nominal Value Unit 52 Nominal Value Unit 2.00 MPa 200 % Nominal Value Unit < 40.0

Loading 1 (10 N)

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

