

KMI PBS KM802A

Polybutylene Succinate

KMI Group Inc.

Message:

KMI PBS KM802A is a Polybutylene Succinate (PBS) product. It can be processed by extrusion or sheet extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Sheet. Primary characteristic: eco-friendly/green.

General Information	
Features	Biodegradable
Uses	Sheet
Appearance	White
	Yellow
Forms	Granules
Processing Method	Extrusion
	Sheet Extrusion

Physical	Nominal Value	Unit	Test Method
Density	1.20 to 1.28	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR)	< 10	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	25.0 to 30.0	MPa	ISO 527-2
Tensile Strain (Break)	> 300	%	ISO 527-2
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	> 12	kJ/m ²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	> 60.0	°C	ISO 868
Melting Temperature (DSC)	90.0 to 100	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT